

DBI-SALA®
ROPE-SAFE™ ROPE GRAB

SECURITY, SAFETY AND CONFIDENCE



8700570 | MODEL SHOWN

For exceptional usability, performance and
protection on kernmantle rope lifelines



THE ULTIMATE IN FALL PROTECTION

PRODUCT BROCHURE

ADVANCED PERFORMANCE AND SAFETY

DBI-SALA is excited to announce the first rope grab of its kind, a truly global product, certified to multiple world standards providing advanced protection to workers at height.

The Rope-Safe takes rope grabs to the next level. The unique kernmantle rope grab provides the versatility of easily switching between an automatic or manual rope grab and features a built in anti-panic grip.



Compliant to ANSI Z359.1, ANSI A10.32, OSHA 1926.500

BUILT IN ANTI-PANIC GRIP

- Anti-panic grip function engages to arrest a fall even if the user grasps the rope grab in a way that interferes with the primary brake
- Patented inertia cam engages the device from the action of a fall regardless of operation mode

OPERATION SWITCH

- Easily switch from automatic to manual and back with a push of a button, even while wearing gloves

SWIVEL COVER

- Easy attachment and detachment to lifeline without disconnecting from the user

GRAVITY LATCH

- Helps avoid the possibility of attaching to the lifeline in the wrong direction

NON ABRASIVE CAM

- Non-abrasive cam prevents premature wear and tear of rope

TRIPLE ACTION CARABINER

- Lightweight, triple action carabiner
- 3,600 lb. (16 kN) gate strength

SHOCK PACK

- 310 lb. (141 kg) capacity
- Integrated shock pack limits arresting forces 1,348 lbs. (6 kN)

INTEGRAL SWIVEL

- Allows the device to travel freely on the lifeline regardless of the harness "D" ring orientation

SHOCK ABSORBING LANYARD

- 1 ft (.3 m) lanyard
- 2 ft (.6 m) lanyard
- 3 ft (.9 m) lanyard

GENERAL INDUSTRY



8700570

Rope-Safe Rope Grab 1 ft. (.3 m) shock absorbing lanyard and aluminum triple action captive eye carabiner



8700571

Rope-Safe Rope Grab 2 ft. (.6 m) shock absorbing lanyard and aluminum triple action captive eye carabiner



8700572

Rope-Safe Rope Grab 3 ft. (.9 m) shock absorbing lanyard and aluminum triple action captive eye carabiner



8700620

Rope-Safe Rope Grab 1 ft. (.3 m) shock absorbing lanyard with towable cord and aluminum triple action captive eye carabiner



8700643

Rope-Safe Rope Grab 2 ft. (.6 m) shock absorbing lanyard with towable cord and aluminum triple action captive eye carabiner



8700621

Rope-Safe Rope Grab 3 ft. (.9 m) shock absorbing lanyard with towable cord and aluminum triple action captive eye carabiner

PRODUCT SPECIFICATIONS

LIFELINE	Diameter: 27/64 in (10.5mm) - 1/2 in (13mm)	
	Construction: Kernmantle	
	Material: Nylon/Nylon or Polyester/Nylon; (sheath/core)	
WEIGHT with Lanyard and Connectors	8700570: 30.3 oz (860 gms)	8700620: 30.3 oz (860 gms)
	8700571: 33.3 oz (944 gms)	8700643: 33.3 oz (944 gms)
	8700572: 35.3 oz (1000 gms)	8700621: 35.3 oz (1000 gms)
CONNECTOR	ANSI compliant, captive eye pin, carabiner	
	Minimum breaking strength 5000 lb (22.2 kN) spine, 3600 lb (16 kN) gate	
	Material: Aluminum	
	Gate lock: Triple action	
OPERATION	Switchable, manual & automatic	
	Anti-Panic Grip and right side direction protection (Gravity latch on cover)	

Designed and tested for use on 27/64 - 1/2 in (10.5 - 13 mm) kernmantle rope.



Capital Safety
 USA: 800 328 6146
www.capitalsafety.com info@capitalsafety.com
 CANADA: 800 387 7484
csgcustomerservice@capitalsafety.com

I-SAFE ENABLED

