

Swiveling Standing Seam Roof Anchor



*Non-penetrating
design won't
damage the roof!*

*A roof anchor
that combines
ease of installation
with performance,
safety and
exceptional
value!*

Versatile Design Fits Most Roofs Providing 360° of Protection.

- **Portable and reusable anchor for use on sloped or flat structural standing seam roofs**
- **Fits seam spacing of 12.0" to 24.0" (30cm-61cm) allowing maximum installation flexibility**
- **Lightweight system installs in minutes, ready for use with no special tools**
- **Non-penetrating clamp design won't damage the roofing material ensuring worry free installation**
- **Universal self retracting lifeline (SRL) cradle fits most SRL's including Protecta and DBI-SALA brands for added versatility**
- **Swivels a full 360° providing maximum mobility and protection**
- **Durable steel construction with painted finish for long lasting durability**
- **Meets or exceeds all applicable industry standards including OSHA and ANSI Z359.1**

Swiveling Standing Seam Roof Anchor



Ultimate Protection and Safety

When you are up on a structural standing seam roof, whether flat or sloped, your fall protection system needs specialized components to keep you safe without damaging the roof. Our Standing Seam Roof Anchor is a simple and safe commercial construction solution. This anchor can have significant impact on jobsite safety while reducing injuries and costly insurance company claims. The unique design provides workers with a fall protection anchor during initial construction, as well as during future maintenance.

Simple, Fast and Efficient Installation

This system installs in minutes with no special tools or equipment required. The roof anchor will adjust to fit any structural standing seam roofing material 24 gauge or thicker with a seam spacing ranging from 12.0" to 24.0" (30cm-61cm), eliminating the need for numerous systems. Simply adjust the clamp plates to match the seam width, position the clamps on the seam and use a torque wrench with a 3/16-inch hex bit (provided with the clamps) to tighten bolts. Refer to the user instruction manual for complete installation details.

Easy to Use, Relocate and Store

Simply attach the anchor, install the SRL into the cradle, connect the SRL to your harness and you are ready to go. The universal Self Retracting Lifeline (SRL) cradle allows virtually any SRL to be used in conjunction with the Standing Seam Anchor. All components are reusable and ready for relocation or storage.

Standards and Warranty

Complies with OSHA and ANSI Z359.1 requirements. Reliability that saves you worry, time and money. The reputation of Protecta stands behind every one of our products, supported by a two year warranty on parts and workmanship.

Capital Safety

USA: 800.328.6146
Canada: 800.387.7484
Latin America: +1 651.385.4301
Asia: +65 6558 7758
Australia: 1800 245 002
New Zealand: 0800 212 505
Europe, Middle East, Africa: +33 (0)4 97 10 00 10
Northern Europe: +44 (0) 1928 571324

www.capitalsafety.com • info@capitalsafety.com

MODEL 2190001



Shown with AD Series Protecta JRG™ SRL. Must order Self Retracting Lifeline separately.

Roof Anchor Models:

2190001: Standing Seam Roof Anchor, for use with self retracting lifeline (Order Separately), fits 12"-24" (30cm-61cm) seam spacing (2190001C in Canada)

Specifications:

Material: Painted steel frame, aluminum clamps
Capacity: One User, 310 lbs. (139.5 kg) **Weight:** 23 lbs. (10.4 Kg)
Size: 30" x 12" x 8.45" (76cm x 30cm x 21cm) **Compliance:** OSHA and ANSI Z359.1.

Anchor Installation Detail

